

Appl. No. : 09/911,253
Filed : July 23, 2001

AMENDMENTS TO THE CLAIMS

1. (Withdrawn) A cleavable signal element, comprising:
a cleavable spacer, said cleavable spacer having a substrate-attaching end, a signal-responsive end, and a cleavage site intermediate said substrate-attaching end and said signal responsive end;
a signal responsive moiety;
a first side member adapted to bind a first site on a chosen analyte; and
a second side member adapted to bind a second site of said chosen analyte;
wherein said signal responsive moiety is attached to said cleavable spacer at said signal responsive end, said first side member is attached to said cleavable spacer intermediate said signal responsive end and said cleavage site, and said second side member is attached to said cleavable spacer intermediate said cleavage site and said substrate attaching end.
2. (Withdrawn) The cleavable signal element of claim 1, wherein said signal responsive moiety is adapted to reflect or scatter incident light.
3. (Withdrawn) The cleavable signal element of claim 2, wherein said signal responsive moiety is a metal microsphere.
4. (Withdrawn) The cleavable signal element of claim 3, wherein said metal microsphere consists essentially of a metal selected from the group consisting of gold, silver, nickel, platinum, chromium and copper.
5. (Withdrawn) The cleavable signal element of claim 4, wherein said metal microsphere consists essentially of gold.
6. (Withdrawn) The cleavable signal element of claim 5, wherein said gold microsphere has a diameter between 1 nm - 10 μ m.
7. (Withdrawn) The cleavable signal element of claim 6, wherein said gold microsphere has a diameter between 0.5 - 5 μ m.
8. (Withdrawn) The cleavable signal element of claim 7, wherein said gold microsphere has a diameter between 1 - 3 μ m.

Appl. No. : 09/911,253
Filed : July 23, 2001

9. (Withdrawn) The cleavable signal element of claim 1, wherein said cleavage site is susceptible to chemical cleavage.

10. (Withdrawn) The cleavable signal element of claim 9, wherein said chemically susceptible cleavage site includes at least one siloxane group.

11. (Withdrawn) The cleavable signal element of claim 1, wherein said first side member and said second side member include oligonucleotides.

12. (Withdrawn) The cleavable signal element of claim 11, wherein said first and second side member oligonucleotides are 5mers - 20mers.

13. (Withdrawn) The cleavable signal element of claim 12, wherein said first and second side member oligonucleotides are 8mers - 17mers.

14. (Withdrawn) The cleavable signal element of claim 12, wherein said first and second side member oligonucleotides are 8mers - 12mers.

15. (Withdrawn) The cleavable signal element of claim 1, wherein said first side member includes a first member of a first specific binding pair, said second side member includes a first member of a second specific binding pair, and

said second member of said first specific binding pair and said second member of said second specific binding pair are each present on the surface of a single analyte.

16. (Withdrawn) The cleavable signal element of claim 15, wherein said first member of said first specific binding pair includes a first antibody, antibody fragment, or antibody derivative, and said first member of said second specific binding pair includes a second antibody, antibody fragment, or antibody derivative.

17. (Withdrawn) The cleavable signal element of claim 15, wherein said first side member includes a first side member oligonucleotide, said second side member includes a second side member oligonucleotide, said first member of said first specific binding pair includes a first binding pair oligonucleotide,

said first member of said second specific binding pair includes a second binding pair oligonucleotide, and

Appl. No. : 09/911,253
Filed : July 23, 2001

said first side member oligonucleotide includes sequence complementary to sequence included in said first binding pair oligonucleotide, said second side member oligonucleotide includes sequence complementary to sequence included in said second binding pair oligonucleotide, and said complementary sequences are noncovalently associated.

18. (Withdrawn) An assay device for detecting analyte, comprising:

an optical disk having analyte-specific signal elements disposed readably thereon.

19. (Withdrawn) The assay device of claim 18, wherein said analyte-specific signal elements are cleavable.

20. (Withdrawn) An assay device for detecting analyte, comprising:

an optical disk having analyte-specific signal elements disposed readably thereon,

wherein said analyte-specific signal elements are cleavable signal elements according to any one of claims 1 - 17.

21-33. (Cancelled).

34. (Currently Amended) An assay system for detecting the presence of an analyte comprising:

an optical disc comprising

a wave guide comprising

having a radiation inlet and a radiation outlet, said wave guide including a radiation transmissive body of said disk which extends between said inlet and said outlet including a first exterior surface and a second exterior surface;

an inlet where radiation is directed into said waveguide, wherein said waveguide is configured to propagate radiation through said transmissive body by internal reflection, and configured such that a portion of said radiation being transmitted through said transmissive body escapes through said first exterior surface; and

a sample channel configured to receive a sample, said sample channel in fluid communication with said first exterior surface;

Appl. No. : 09/911,253
Filed : July 23, 2001

a radiation source ~~that configured to~~ provides radiation of a given intensity to said inlet of said waveguide; ~~wave-guide inlet, a portion of said radiation being transmitted radially through said body from said inlet to said outlet and a portion of said radiation escaping through said exterior surface to thereby reduce said intensity of the radiation at said wave-guide outlet;~~

a plurality of spatially addressable assay sites located on said first exterior surface, each of said assay sites comprising one or more signal elements attached to the said first exterior surface of said wave-guide on the outside of said radiation transmissive body, said signal elements being capable of reacting with said an analyte to form analyte bound signal elements, said analyte bound signal elements which are capable of reflecting providing a differing degree of radiation escape that escapes through said first exterior surface back through said first exterior surface and through said second exterior surface, then said signal elements which are not bound to said analyte; and

a detector configured to detect for measuring the change in radiation intensity at said wave-guide outlet or the change in the radiation escaping through said the second exterior surface of said transmissive body wave-guide at said plurality of assay sites to provide detection of determine-identify said analyte that has reacted with said signal elements to form said analyte bound signal elements.

35. (Currently Amended) An assay system for detecting the presence of an analyte according to claim 34 wherein said signal elements are located at a given distance from said first exterior surface and said analyte bound signal elements are tethered to said first exterior surface to provide tethered signal elements which are located closer to said exterior surface than said signal elements which are not tethered thereto.

36. (Previously presented) An assay system for detecting the presence of an analyte according to claim 35 wherein said signal element comprises:

a signal responsive moiety;

a spacer for attaching said signal responsive moiety to said exterior surface of said wave guide, said spacer having an end attached to said exterior surface and an end attached to said signal responsive moiety;

Appl. No. : 09/911,253
Filed : July 23, 2001

a first anchoring member having a first end attached to said exterior surface and a second end adapted to bind on a first site on a chosen analyte; and

a second anchoring member having a first end attached to said signal responsive moiety and a second end adapted to bind on a second site on said chosen analyte; and

the signal responsive moiety becoming tethered to said exterior surface only when said first and second anchoring members are bound to said chosen analyte.

37. (Previously presented) An assay system for detecting the presence of an analyte according to claim 36 wherein said spacer is cleavable for releasably attaching said signal responsive moiety to said exterior surface, said cleavable spacer including a cleavage site intermediate the end of said spacer attached to said exterior surface and the end of said spacer attached to said signal responsive moiety, said signal responsive moiety remaining bound to said exterior surface after cleavage at said cleavage site only when said first and second anchoring members are bound to said chosen analyte.

38. (Previously presented) An assay system for detecting the presence of an analyte according to claim 34 that includes a detector that is capable of identifying analyte bound signal elements.

39. (Previously presented) An assay system for detecting the presence of an analyte according to claim 34 wherein said signal elements comprise:

a first signal element located in a first assay sector which is capable of reacting with a first chosen analyte to form a first bound analyte; and

a second signal element located in a second assay sector which is capable of reacting with a second chosen analyte to form a second bound analyte.

40. (Canceled)

41. (Currently amended) An assay system for detecting the presence of an analyte according to claim 40-34 wherein said optical disc ~~includes-comprises~~ encoded computer software.

42. (Canceled)

43. (Currently Amended) An assay system for detecting the presence of an analyte according to claim 34 wherein said first exterior surface is hydrophilic.

Appl. No. : 09/911,253
Filed : July 23, 2001

44. (Withdrawn) An assay device for use in detecting the presence of an analyte comprising:

a wave guide having a radiation inlet and a radiation outlet, said wave guide including an exterior surface defining a radiation transmissive body which extends between said inlet and said outlet such that radiation is transmitted radially through said body from said inlet to said outlet, a portion of said radially transmitted radiation escaping through said exterior surface; and

one or more signal elements attached to the exterior surface of said wave guide on the outside of said radiation transmissive body, said signal elements being capable of reacting with said analyte to form analyte bound signal elements, said analyte bound signal elements providing a differing degree of radiation escape through said exterior surface than said signal elements which are not bound to said analyte.

45. (Withdrawn) An assay device for detecting the presence of an analyte according to claim 44 wherein said signal element comprises:

a signal responsive moiety;

a spacer for attaching said signal responsive moiety to said exterior surface of said wave guide, said spacer having an end attached to said exterior surface and an end attached to said signal responsive moiety;

a first anchoring member having a first end attached to said exterior surface and a second end adapted to bind on a first site on a chosen analyte;

a second anchoring member having a first end attached to said signal responsive moiety and a second end adapted to bind on a second site on said chosen analyte; and

the signal responsive moiety becoming tethered to said exterior surface only when said first and second anchoring members are bound to said chosen analyte.

46. (Withdrawn) An assay device for detecting the presence of and analyte according to claim 45 wherein said spacer is cleavable for releasably attaching said signal responsive moiety to said exterior surface, said cleavable spacer including a cleavage site intermediate the end of said spacer attached to said exterior surface and the end of said spacer attached to said signal responsive moiety, said signal responsive moiety remaining bound to said exterior surface after cleavage at said cleavage site only when said first and second anchoring members are bound

Appl. No. : 09/911,253
Filed : July 23, 2001

to said chosen analyte.

47. (Withdrawn) An assay device for detecting the presence of an analyte according to claim 44 wherein said wave guide is located in a disc.

48. (Withdrawn) An assay device for detecting the presence of an analyte according to claim 47 wherein said disc includes encoded computer software.

49. (Withdrawn) An assay device for detecting the presence of an analyte according to claim 48 wherein said disc is an optical disc.

50. (Withdrawn) An assay device for detecting the presence of an analyte according to claim 44 wherein said signal elements comprise:

a first signal element located in a first assay sector which is capable of reacting with a first chosen analyte to form a first bound analyte; and

a second signal element located in a second assay sector which is capable of reacting with a second chosen analyte to form a second bound analyte.

51. (Withdrawn) An assay device for detecting the presence of an analyte according to claim 45 wherein said exterior surface is hydrophilic.

52. (Withdrawn) A method for detecting the presence of an analyte comprising the steps of:

providing a wave guide having a radiation inlet and a radiation outlet, said wave guide including an exterior surface defining a radiation transmissive body which extends between said inlet and said outlet, said exterior surface allowing radiation to escape from said transmissive body, said wave guide including one or more signal elements attached to the exterior surface of said wave guide on the outside of said radiation transmissive body, said one or more signal elements being capable of reacting with said analyte to form one or more analyte bound signal elements, said analyte bound signal elements providing a differing degree of radiation escape through said exterior surface than said signal elements which are not bound to said analyte;

exposing said signal elements to a sample for a sufficient time to allow analyte in said sample to react with said one or more signal elements to form said analyte bound signal elements;

providing radiation of a given intensity to said wave guide inlet; and

Appl. No. : 09/911,253
Filed : July 23, 2001

measuring the intensity of radiation at said wave guide outlet or the intensity of radiation escaping through said exterior surface of said wave guide to provide detection of said analyte that has reacted with said signal elements to form said analyte bound signal elements.

53. (Withdrawn) A method for detecting the presence of an analyte according to claim 52 wherein said signal elements are located at a given distance from said exterior surface and said analyte bound signal elements are tethered to said exterior surface to provide tethered signal elements which are located closer to said exterior surface than said signal elements which are not tethered thereto.

54. (Withdrawn) An method for detecting the presence of an analyte according to claim 53 wherein said signal element comprises:

a signal responsive moiety;

a spacer for attaching said signal responsive moiety to said exterior surface of said wave guide, said spacer having an end attached to said exterior surface and an end attached to said signal responsive moiety;

a first anchoring member having a first end attached to said exterior surface and a second end adapted to bind on a first site on a chosen analyte;

a second anchoring member having a first end attached to said signal responsive moiety and a second end adapted to bind on a second site on said chosen analyte; and

the signal responsive moiety becoming tethered to said exterior surface only when said first and second anchoring members are bound to said chosen analyte.

55. (Withdrawn) A method for detecting the presence of an analyte according to claim 54 wherein said spacer is cleavable for releasably attaching said signal responsive moiety to said exterior surface, said cleavable spacer including a cleavage site intermediate the end of said spacer attached to said exterior surface and the end of said spacer attached to said signal responsive moiety, said signal responsive moiety remaining bound to said exterior surface after cleavage at said cleavage site only when said first and second anchoring members are bound to said chosen analyte.

56. (Withdrawn) A method for detecting the presence of an analyte according to claim 52 which includes the further step of identifying which signal elements have become

Appl. No. : 09/911,253
Filed : July 23, 2001

analyte bound signal elements.

57. (Withdrawn) A method for detecting the presence of an analyte according to claim 55 which includes the further step of identifying which signal elements have become analyte bound signal elements, said identification step including the step of removing signal elements from said exterior surface by cleaving said spacers at said cleavage sites so that only analyte bound signal elements remain attached to said exterior surface.

58. (Withdrawn) A non-specific method for monitoring a sample for the presence of a plurality of analytes, said method comprising the steps of:

providing a wave guide having a radiation inlet and a radiation outlet, said wave guide including an exterior surface defining a radiation transmissive body which extends between said inlet and said outlet, said exterior surface allowing radiation to escape from said transmissive body, said wave guide including first and second signal elements attached to the exterior surface of said wave guide on the outside of said radiation transmissive body, said first and second signal elements being located in first and second assay sectors and being capable of reacting with first and second analytes to form first and second analyte bound signal elements, said first and second analyte bound signal elements providing a differing degree of radiation escape through said exterior surface than said signal elements which are not bound to said analyte;

continuously exposing said first and second signal elements to a sample to allow any first or second analyte in said sample to react with said first or second signal elements to form said first or second analyte bound signal elements;

providing radiation of a given intensity to said wave guide inlet; and

measuring the intensity of radiation at said wave guide outlet or the intensity of radiation escaping through said exterior surface of said wave guide to provide non-specific detection of said first analyte and/or said second analyte that has reacted with said signal elements to form said first and/or second analyte bound signal elements.

59. (Withdrawn) A specific method for monitoring a sample for the presence of a plurality of analytes, said method comprising the steps of non-specifically identifying the presence of an analyte in accordance with the method set forth in claim 58 and then specifically identifying the presence of a given analyte, said step of specifically identifying said analyte

Appl. No. : 09/911,253
Filed : July 23, 2001

including removal of signal elements from said exterior surface which are not analyte bound signal elements.

60. (Withdrawn) A specific method for monitoring a sample for the presence of a plurality of analytes according to claim 59 wherein said signal element includes:

a signal responsive moiety;

a spacer for attaching said signal responsive moiety to said exterior surface of said wave guide, said spacer having an end attached to said exterior surface and an end attached to said signal responsive moiety, said spacer further including a cleavage site located between said end attached to said exterior surface and said end attached to said signal responsive moiety;

a first anchoring member having a first end attached to said exterior surface and a second end adapted to bind on a first site on said first or second analyte;

a second anchoring member having a first end attached to said signal responsive moiety and a second end adapted to bind on a second site on said first or second analyte;
and

the signal responsive moiety becoming tethered to said exterior surface only when said first and second anchoring members are bound to said first or second analyte, said step of removing signal elements from said exterior surface which are not analyte bound including the step of cleaving said spacers at said cleavage sites.

61. (Withdrawn) A radiation detector readable disk comprising a wave guide having a radiation inlet and a radiation outlet, said wave guide including a radiation transmission solid body of said disk which extends between said inlet and said outlet and an analyte detection surface on the exterior of said body.

62. (Withdrawn) The disk of claim 61 further comprising one or more signal elements attached to said surface.

63. (Withdrawn) The disk of claim 62 wherein said wave guide is provided such that a portion of radiation transmitted through said body from said inlet to said outlet escapes through said surface, said signal elements being capable of reacting with an analyte to form analyte bound signal elements, said analyte bound signal elements providing a differing degree of radiation escape through said surface than said signal elements which are not bound to an analyte.

Appl. No. : 09/911,253
Filed : July 23, 2001

64. (Withdrawn) The disk of claim 63 wherein said signal elements are located at a given distance from said surface and said analyte bound signal elements are tethered to said surface to provide tethered signal elements which are located closer to said surface than said signal elements which are not tethered thereto.

65. (Withdrawn) The disk of claim 63 wherein said signal element comprises:

a signal responsive moiety;

a spacer for attaching said signal responsive moiety to said surface of said wave guide, said spacer having an end attached to said surface and an end attached to said signal responsive moiety;

a first anchoring member having a first end attached to said surface and a second end adapted to bind on a first site on a chosen analyte;

a second anchoring member having a first end attached to said signal responsive moiety and a second end adapted to bind on a second site on said chosen analyte; and

the signal responsive moiety becoming tethered to said surface only when said first and second anchoring members are bound to said chosen analyte.

66. (Withdrawn) The disk of claim 65 wherein said spacer is cleavable for releasably attaching said signal responsive moiety to said surface, said cleavable spacer including a cleavage site intermediate the end of said spacer attached to said surface and the end of said spacer attached to said signal responsive moiety, said signal responsive moiety remaining bound to said surface after cleavage at said cleavage site only when said first and second anchoring members are bound to said chosen analyte.

67. (Withdrawn) The disk of claim 63 wherein one or more signal elements attached to the surface of said wave guide on the outside of said radiation transmissive body, said signal elements being capable of reacting with said analyte to form analyte bound signal elements, said analyte bound signal elements providing a differing degree of radiation escape through said surface than said signal elements which are not bound to said analyte.

68. (Withdrawn) The disk of any of claims 61 through 67 wherein said signal elements are provided in a spatially addressable pattern.

69. (Withdrawn) The disk of any one of claims 61 through 67 wherein said disk further comprises encoded software.

Appl. No. : 09/911,253
Filed : July 23, 2001

70. (Withdrawn) The disk of anyone one of claims 63 through 67 wherein said wave guide surface is provided as part of a chamber within said disk.

71. (Withdrawn) The disk of claim 68 when said disk further comprises software encoded in an area of said disk which is spatially distinct from the pattern of said elements.

72. (Withdrawn) An assay device comprising:

a substrate of a laser detector readable disk;

a wave guide located in said substrate and having a radiation inlet and a radiation outlet, said wave guide including a radiation transmitting body of said substrate which extends between said inlet and said outlet; and

said wave guide including an exterior surface such that radiation is transmitted through said body from said inlet to said outlet and a portion of said radiation escapes through said exterior surface.

73. (Withdrawn) The assay device of claim 72 further comprising a plurality of analyte binding elements attached to said substrate.

74. (Withdrawn) The assay device of claim 73 wherein said plurality of analyte binding elements are attached to said substrate in a spatially addressable pattern.

75. (Withdrawn) The assay device of any one of claims 72 through 74 wherein said disk further comprises computer software encoded upon said substrate.

76. (Withdrawn) The assay device of claim 74 wherein said disk further comprises computer software encoded upon said substrate in an area of said substrate which is spatially distinct from said spatially addressable pattern of said elements.

77. (Withdrawn) The assay device of claim 72 comprising:

one or more individual assay sectors segregated within said substrate; and

a sample inlet port associated with each of said one or more assay sectors.

78. (Withdrawn) The assay device of claim 77 wherein one or more analyte binding elements are provided within each of said one or more individual assay sectors.

79. (Withdrawn) The assay device of claim 78 wherein said one or more analyte binding elements include cleavable signal elements having a cleavable spacer and a signal responsive moiety.

80. (Withdrawn) The assay device of claim 75 wherein said software includes

Appl. No. : 09/911,253
Filed : July 23, 2001

information for controlling the correct tracking of an incident laser.

81. (New) The assay system of claim 34, wherein the optical disc further comprises a mirror positioned to direct radiation from said radiation source into said inlet of said waveguide.

82. (New) The assay system of claim 34, wherein the waveguide further comprises a diffraction grating to direct radiation from said radiation source into said inlet of said waveguide.

83. (New) The assay system of claim 34, wherein said optical disc further comprises a transmissive substrate, and wherein said transmissive body comprises a portion of said transmissive substrate.

84. (New) The assay system of claim 34, wherein said radiation transmissive body comprises a hollow interior geometry.

85. (New) The assay system of claim 34, wherein said radiation transmissive body is disposed radially on said optical disc.